

Central coolant duct, length: 330 mm

Zentralbohrung, Länge: 330 mm

□ raw / roh | • ground / geschliffen

D mm	D h6 mm	d mm	a mm	K40UF 7337	K6UF 7150
4.5 +0.30		0.60 ±0.10	0.15	□	□
4.501 +0.30		1.00 ±0.15	0.15		□
6.3 +0.30	6.0	1.00 ±0.15	0.15	□ •	□
6.301 +0.30		1.80 ±0.15	0.15	□	□
8.3 +0.30	8.0	1.30 ±0.15	0.15	□ •	□
8.301 +0.30		2.50 ±0.15	0.15	□	□
8.302 +0.30		1.80 ±0.15	0.15		□
10.3 +0.40	10.0	2.00 ±0.20	0.20	□ •	□
10.301 +0.40		3.00 ±0.20	0.20	□	□
12.3 +0.40	12.0	2.00 ±0.20	0.20	□ •	□
12.301 +0.40		3.00 ±0.20	0.20	□	□
14.3 +0.40	14.0	2.00 ±0.20	0.25	□ •	□
14.301 +0.40		3.00 ±0.20	0.25	□	□
16.3 +0.50	16.0	2.00 ±0.20	0.25	□ •	□
16.301 +0.50		2.50 ±0.20	0.25	□	□
16.302 +0.50		4.00 ±0.30	0.25	□	□
16.303 +0.50		3.00 ±0.25	0.25	□	
18.3 +0.50	18.0	3.00 ±0.25	0.25	□ •	□
18.301 +0.50		4.00 ±0.25	0.25		□
20.3 +0.50	20.0	3.00 ±0.25	0.30	□ •	□
20.301 +0.50		4.00 ±0.25	0.30		□
22.3 +0.50	22.0	3.00 ±0.25	0.30	□ •	□
24.3 +0.50	24.0	4.00 ±0.30	0.30	□ •	□
25.3 +0.50	25.0	4.00 ±0.30	0.30	□ •	□
26.3 +0.50	26.0	4.00 ±0.30	0.30	□ •	□
28.3 +0.50	28.0	4.00 ±0.30	0.30	□ •	□
30.3 +0.50	30.0	5.00 ±0.35	0.30	□ •	□
32.3 +0.50	32.0	5.00 ±0.35	0.30	□ •	□

