

# Rods / Rundstäbe

2 parallel coolant ducts, length: 310 mm

2 parallele Kühlkanäle, Länge: 310 mm

□ raw / roh | • ground / geschliffen

D mm	D h6 mm	BC / TK mm	d mm	a mm	K40UF 7307	K44UF 7323	K20F 7123
3.2 +0.30		1.20 -0.10	0.50 ±0.10	0.10	□		
4.2 +0.30		1.80 -0.15	0.80 ±0.10	0.10	□	□	□
4.7 +0.30		2.00 -0.15	0.80 ±0.10	0.13			□
5.2 +0.30		2.00 -0.15	0.80 ±0.10	0.13	□	□	□
6.3 +0.30	6.0	3.00 -0.20	1.00 ±0.10	0.15	□ •	□	□
7.3 +0.30		3.50 -0.20	1.00 ±0.15	0.15	□	□	□
8.3 +0.30	8.0	4.00 -0.30	1.00 ±0.15	0.15	□ •	□	□
9.3 +0.30		4.00 -0.30	1.40 ±0.15	0.20	□	□	□
10.3 +0.30	10.0	5.00 -0.30	1.40 ±0.15	0.20	□ •	□	□
11.3 +0.40		5.00 -0.30	1.40 ±0.20	0.28	□	□	□
12.3 +0.40	12.0	6.00 -0.30	1.75 ±0.20	0.30	□ •	□	□
13.3 +0.40	13.0	6.00 -0.30	1.75 ±0.20	0.34	□ •	□	□
14.3 +0.40	14.0	7.00 -0.30	1.75 ±0.20	0.37	□ •	□	□
15.3 +0.40	15.0	7.00 -0.30	2.00 ±0.20	0.40	□ •	□	□
16.3 +0.40	16.0	8.00 -0.30	2.00 ±0.20	0.40	□ •	□	□
17.3 +0.50		8.00 -0.30	2.00 ±0.20	0.47	□	□	□
18.3 +0.50	18.0	9.00 -0.30	2.00 ±0.20	0.50	□ •	□	□
19.3 +0.50		9.00 -0.30	2.00 ±0.20	0.50	□	□	□
20.4 +0.50	20.0	10.00 -0.40	3.00 ±0.25	0.50	□ •	□	□
21.4 +0.50	21.0	10.00 -0.40	3.00 ±0.25	0.50	□ •	□	□
22.4 +0.50	22.0	11.00 -0.40	3.00 ±0.25	0.50	□ •	□	□
23.4 +0.50	23.0	11.00 -0.40	3.00 ±0.25	0.50	□ •	□	□
24.4 +0.50		12.00 -0.50	3.00 ±0.25	0.50	□	□	□
25.4 +0.50	25.0	12.00 -0.50	3.00 ±0.30	0.50	□ •	□	□
26.4 +0.50	26.0	13.00 -0.50	3.00 ±0.30	0.50	□ •	□	□
28.4 +0.50	28.0	14.00 -0.50	3.00 ±0.30	0.50	□ •	□	
30.4 +0.50	30.0	14.00 -0.50	3.00 ±0.30	0.50	□ •	□	
32.4 +0.50	32.0	14.00 -0.50	3.00 ±0.30	0.50	□ •	□	□
34.4 +0.50		14.00 -0.50	3.00 ±0.30	0.50	□	□	

