

## 2 parallel coolant ducts, length: 330 mm

2 parallele Kühlkanäle, Länge: 330 mm

□ raw / roh | • ground / geschliffen

D mm	D h6 mm	BC / TK mm	d mm	a mm	K40UF 7326
4.2 +0.20		1.80 -0.15	0.80 ±0.10	0.10	□
5.2 +0.20		2.00 -0.15	0.80 ±0.10	0.13	□
6.3 +0.20	6.0	3.00 -0.20	1.00 ±0.10	0.15	□ •
7.3 +0.20		3.50 -0.20	1.00 ±0.15	0.15	□
8.3 +0.20	8.0	4.00 -0.30	1.00 ±0.15	0.15	□ •
9.3 +0.20		4.00 -0.30	1.40 ±0.15	0.20	□
10.3 +0.20	10.0	5.00 -0.30	1.40 ±0.15	0.20	□ •
11.3 +0.20		5.00 -0.30	1.40 ±0.20	0.28	□
12.3 +0.20	12.0	6.00 -0.30	1.75 ±0.20	0.30	□ •
13.3 +0.20		6.00 -0.30	1.75 ±0.20	0.34	□
14.3 +0.20	14.0	7.00 -0.30	1.75 ±0.20	0.37	□ •
15.3 +0.20		7.00 -0.30	2.00 ±0.20	0.40	□
16.3 +0.20	16.0	8.00 -0.30	2.00 ±0.20	0.40	□ •
17.3 +0.20		8.00 -0.30	2.00 ±0.20	0.47	□
18.3 +0.20	18.0	9.00 -0.30	2.00 ±0.20	0.50	□ •
19.3 +0.20		9.00 -0.30	2.00 ±0.20	0.50	□
20.4 +0.20	20.0	10.00 -0.40	2.50 ±0.25	0.50	□ •
21.4 +0.20		10.00 -0.40	2.50 ±0.25	0.50	□
22.4 +0.20		11.00 -0.40	2.50 ±0.25	0.50	□
23.4 +0.20		11.00 -0.40	2.50 ±0.25	0.50	□
24.4 +0.20		12.00 -0.50	2.50 ±0.25	0.50	□
25.4 +0.20	25.0	12.00 -0.50	3.00 ±0.30	0.50	□ •
26.4 +0.20		13.00 -0.50	3.00 ±0.30	0.50	□
30.4 +0.20		14.00 -0.50	3.00 ±0.30	0.50	□

