

Rods / Rundstäbe

2 parallel coolant ducts, length: 310 mm (reduced bolt circle)

2 parallele Kühlkanäle, Länge: 310 mm (eingengter Teilkreis)

□ raw / roh | ● ground / geschliffen

D mm	D h6 mm	BC / TK mm	d mm	a mm	K40UF 7308	K44UF 7324	K20F 7130
6.3 +0.30	6.0	1.50 -0.20	0.80 ±0.10	0.15	□ ●	□	□
7.3 +0.30		1.50 -0.20	0.80 ±0.10	0.15	□	□	□
8.3 +0.30	8.0	2.60 -0.30	1.00 ±0.10	0.15	□ ●	□	□
8.315 +0.30		0.90 -0.70	0.30 ±0.05	0.08	□	□	
8.320 +0.30		2.00 -0.30	0.80 ±0.05	0.15	□	□	
9.3 +0.30		2.60 -0.30	1.00 ±0.10	0.20	□	□	□
10.3 +0.30	10.0	2.60 -0.30	1.00 ±0.10	0.20	□ ●	□	□
11.3 +0.40		3.50 -0.30	1.20 ±0.15	0.28	□	□	□
12.3 +0.40	12.0	3.50 -0.30	1.20 ±0.15	0.30	□ ●	□	□
13.3 +0.40		3.50 -0.30	1.20 ±0.15	0.34	□	□	□
14.3 +0.40	14.0	5.00 -0.30	1.50 ±0.15	0.37	□ ●	□	□
14.8 +0.40		5.00 -0.30	1.50 ±0.15	0.40	□		
15.3 +0.40		5.00 -0.30	1.50 ±0.15	0.40	□	□	□
16.3 +0.40	16.0	5.00 -0.30	1.50 ±0.15	0.47	□ ●	□	□
17.3 +0.50		6.20 -0.30	2.00 ±0.20	0.50	□	□	□
18.3 +0.50	18.0	6.20 -0.30	2.00 ±0.20	0.50	□ ●	□	□
19.3 +0.50		6.20 -0.30	2.00 ±0.20	0.50	□	□	□
20.4 +0.50	20.0	6.20 -0.40	2.00 ±0.20	0.50	□ ●	□	□
21.4 +0.50		6.20 -0.40	2.00 ±0.20	0.50	□	□	□
22.4 +0.50	22.0	6.20 -0.40	2.00 ±0.20	0.50	□ ●	□	□
23.4 +0.50		7.50 -0.40	2.00 ±0.20	0.50	□	□	
24.4 +0.50	24.0	7.50 -0.40	2.00 ±0.20	0.50	□ ●	□	
25.4 +0.50	25.0	7.50 -0.40	2.00 ±0.20	0.50	□	□	
26.4 +0.50	26.0	7.50 -0.40	2.00 ±0.20	0.50	□		

