

Micro-twisted rods / Kleinstverdrallte Rundstäbe

2 coolant ducts

2 Kühlkanäle

— Available in length 330mm and as fix lengths /
In Länge 330mm und als Fixlänge verfügbar

- Only available as fix length / Nur als Fixlänge verfügbar

D mm	BC / TK mm	d mm	Pitch Steig. mm	L
3.3	0.45	0.16	5.44	-
3.3	0.50	0.20	5.44	-
3.3	0.40	0.15	6.00	-
3.3	0.60	0.20	6.80	-
3.3	0.75	0.20	7.60	-
3.3	0.70	0.25	8.16	-
3.3	0.90	0.30	9.00	-
3.3	0.75	0.20	9.80	-
3.3	0.50	0.20	10.10	-
3.3	0.90	0.25	10.76	—
3.3	0.30	0.15	11.23	-
3.3	1.30	0.30	11.23	—
3.3	1.00	0.30	12.20	—
3.3	1.40	0.30	13.49	—
3.3	1.20	0.30	13.60	—
3.3	1.25	0.35	14.20	—
3.3	1.10	0.25	14.50	—
3.3	1.20	0.30	15.00	—
3.3	1.20	0.50	15.00	—
3.3	0.70	0.24	15.44	—
3.3	0.50	0.20	16.32	-
3.3	1.00	0.30	16.32	—
3.3	1.50	0.40	16.32	—
3.3	1.60	0.50	16.32	—
3.3	1.60	0.60	16.32	—
3.3	1.47	0.42	19.10	—
3.3	0.90	0.30	29.30	—
3.3	1.40	0.40	35.17	—
4.3	0.45	0.13	7.25	-
4.3	1.20	0.30	10.50	—
4.3	0.90	0.25	10.76	—
4.3	1.00	0.30	12.20	—
4.3	1.00	0.40	13.00	—
4.3	1.20	0.30	13.50	—

D mm	BC / TK mm	d mm	Pitch Steig. mm	L
4.3	1.50	0.40	13.50	—
4.3	0.50	0.20	14.98	-
4.3	1.00	0.30	14.98	—
4.3	1.50	0.40	14.98	—
4.3	1.60	0.40	14.98	—
4.3	1.90	0.50	16.00	—
4.3	0.90	0.26	17.00	—
4.3	1.60	0.45	17.95	—
4.3	1.50	0.50	19.04	—
4.3	1.60	0.50	19.04	—
4.3	1.57	0.42	19.10	—
4.3	1.15	0.30	19.50	—
4.3	1.25	0.34	21.50	—
4.3	1.70	0.40	21.77	—
4.3	1.75	0.40	21.77	—
4.3	2.20	0.60	21.77	—
4.3	1.70	0.60	21.77	—
4.3	2.10	0.60	21.77	—
4.3	2.20	0.60	21.77	—
4.3	1.30	0.80	22.46	—
4.3	1.40	0.40	24.50	—
4.3	1.47	0.42	25.76	—
4.3	1.50	0.42	28.00	—
4.3	1.70	0.47	32.00	—
4.3	1.40	0.40	46.90	—
6.3	1.00	0.30	10.88	—
6.3	1.40	0.40	32.65	—

