

# Milling cutter blanks / Fräser-Rohlinge

Ground (h6), solid, chamfered one end, for milling cutters DIN 6527

Geschliffen (h6), ohne Kühlkanal, mit einseitiger Fase, für Fräser nach DIN 6527

• ground / geschliffen

D h6 mm	d mm	L mm	Code	K40UF 7127	K44UF 7126	K55SF 7125
3.0	2.4	38.3 +0.5	3.002		•	
3.0	2.4	39.5 +0.5	3.001	•	•	•
3.0	2.4	45.0 +0.5	3.006	•		
3.0	2.4	52.3 +0.5	3.005	•		
3.0	2.4	76.2 +0.5	3.003		•	
4.0	3.4	40.3 +0.5	4.002		•	
4.0	3.4	40.5 +0.5	4.001	•		
4.0	3.4	50.3 +0.5	4.003		•	
4.0	3.4	51.0 +0.5	4.000	•	•	•
4.0	3.4	59.3 +0.5	4.004	•		
4.0	3.4	76.2 +0.5	4.001		•	
5.0	4.0	50.3 +0.5	5.002		•	
5.0	4.0	51.2 +0.5	5.000	•	•	•
5.0	4.0	60.3 +0.5	5.003		•	
5.0	4.0	76.2 +0.5	5.001		•	
6.0	5.0	38.0 +0.5	6.010	•		
6.0	5.0	40.3 +0.5	6.004		•	
6.0	5.0	50.3 +0.5	6.005		•	
6.0	5.0	51.2 +0.5	6.000	•	•	•
6.0	5.0	55.0 +0.5	6.001	•	•	•
6.0	5.0	57.5 +0.5	6.008		•	
6.0	5.0	58.2 +0.5	6.002	•	•	•
6.0	5.0	60.3 +0.5	6.006		•	
6.0	5.0	63.0 +0.5	6.009	•		
6.0	5.0	66.2 +0.5	6.008	•		
6.0	5.0	69.0 +0.5	6.012	•		
6.0	5.0	70.0 +0.5	6.011	•		
6.0	5.0	75.0 +0.5	6.013	•		
6.0	5.0	76.0 +0.5	6.009		•	
6.0	5.0	80.0 +0.5	6.014	•		
6.0	5.0	80.3 +0.5	6.007		•	
6.0	5.0	80.5 +0.5	6.012		•	
6.0	5.0	100.5 +0.5	6.003		•	
6.35	5.4	63.5 +0.5	6.351		•	

D h6 mm	d mm	L mm	Code	K40UF 7127	K44UF 7126	K55SF 7125
7.0	5.0	50.3 +0.5	7.000		•	
7.0	5.0	61.0 +0.5	7.001	•		
7.0	5.0	75.3 +0.5	7.001		•	
8.0	6.0	41.0 +0.5	8.007	•		
8.0	6.0	44.0 +0.5	8.002	•		
8.0	6.0	50.3 +0.5	8.003		•	
8.0	6.0	59.0 +0.5	8.000	•	•	•
8.0	6.0	63.5 +0.5	8.006		•	
8.0	6.0	64.2 +0.5	8.001	•	•	•
8.0	6.0	64.3 +0.5	8.004		•	
8.0	6.0	72.0 +0.5	8.008	•	•	
8.0	6.0	73.5 +0.5	8.011	•		
8.0	6.0	80.0 +0.5	8.009	•		
8.0	6.0	80.3 +0.5	8.005		•	
8.0	6.0	90.0 +0.5	8.010	•		
8.0	6.0	100.5 +0.5	8.007		•	
8.0	6.0	101.2 +0.5	8.005	•		
8.0	6.0	120.5 +0.5	8.002		•	
9.0	7.0	50.3 +0.5	9.000		•	
9.0	7.0	68.0 +0.5	9.002	•		
9.0	7.0	70.3 +0.5	9.001		•	
9.0	7.0	90.3 +0.5	9.002		•	
10.0	8.0	48.0 +0.5	10.009	•		
10.0	8.0	60.3 +0.5	10.004		•	
10.0	8.0	67.2 +0.5	10.000	•	•	•
10.0	8.0	72.5 +0.5	10.007		•	
10.0	8.0	73.2 +0.5	10.002	•	•	•
10.0	8.0	80.3 +0.5	10.005		•	
10.0	8.0	84.0 +0.5	10.010	•		
10.0	8.0	100.0 +0.5	10.011	•		
10.0	8.0	101.0 +0.5	10.001		•	
10.0	8.0	101.2 +0.5	10.004	•		
10.0	8.0	105.0 +0.5	10.012	•		
10.0	8.0	120.5 +0.5	10.006		•	

D h6 mm	d mm	L mm	Code	K40UF 7127	K44UF 7126	K55SF 7125
10.0	8.0	150.5 +0.5	10.003		•	
11.0	9.0	72.0 +0.5	11.000	•		
12.0	10.0	60.3 +0.5	12.003		•	
12.0	10.0	74.2 +0.5	12.000	•	•	•
12.0	10.0	83.5 +0.5	12.006		•	
12.0	10.0	84.2 +0.5	12.001	•	•	•
12.0	10.0	84.3 +0.5	12.004		•	
12.0	10.0	97.0 +0.5	12.008	•		
12.0	10.0	100.0 +0.5	12.005		•	
12.0	10.0	101.2 +0.5	12.004	•		
12.0	10.0	110.0 +0.5	12.009	•		
12.0	10.0	120.0 +0.5	12.010	•		
12.0	10.0	120.5 +0.5	12.002		•	
12.0	10.0	151.0 +0.5	12.007		•	
13.0	11.0	85.0 +0.5	13.001	•		
14.0	12.0	60.3 +0.5	14.004		•	
14.0	12.0	76.2 +0.5	14.001	•	•	•
14.0	12.0	84.0 +0.5	14.003		•	
14.0	12.0	84.2 +0.5	14.000	•	•	•
14.0	12.0	84.3 +0.5	14.002		•	
14.0	12.0	101.2 +0.5	14.004	•		
15.0	12.0	94.0 +0.5	15.001	•		
16.0	13.0	83.2 +0.5	16.001	•	•	•
16.0	13.0	93.0 +0.5	16.002		•	
16.0	13.0	93.2 +0.5	16.000	•	•	•
16.0	13.0	105.5 +0.5	16.009	•		
16.0	13.0	108.0 +0.5	16.007	•		
16.0	13.0	109.2 +0.5	16.006	•		
16.0	13.0	123.0 +0.5	16.008	•		
16.0	13.0	151.0 +0.5	16.003		•	
16.0	13.0	151.2 +0.5	16.004	•		
18.0	15.0	93.0 +0.5	18.002	•	•	•
20.0	17.0	93.2 +0.5	20.000	•	•	•
20.0	17.0	105.0 +0.5	20.001	•	•	•

D h6 mm	d mm	L mm	Code	K40UF 7127	K44UF 7126	K55SF 7125
20.0	17.0	122.0 +0.5	20.007	•		
20.0	17.0	127.2 +0.5	20.006	•		•
20.0	17.0	141.0 +0.5	20.008	•		
20.0	17.0	151.0 +0.5	20.002		•	
25.0	22.0	123.0 +0.5	25.001	•		

